

Mobile Stainless Scissor Lift Tables

Capacity: 100kg-450kg

Optional various table sizes & lift heights

Stainless steel for anti-corrosion applications (Attention: Scissors & Pumps are galvanzied)

Model	Capacity (kg)	Material	Length of table(mm)	Width of table(mm)	Min.height (mm)	Max.height (mm)
TFD15S	100	stainless steel	700	445	250	1220
TF30S	250	stainless steel	815	500	290	890
TFD35S	350	stainless steel	910	500	355	1295
TF50S	450	stainless steel	815	500	290	890



ELECTRIC TABLE LIFTER

Electric Table Truck		1KG=2.2LB 1INCH=25.4MM			
TYPE		ETF30	ETF50	ETF75	ETFD35
Capacity Q	Kg	300	500	750	350
Max.Table Height h _t	mm	880	1025	970	1300
MinTable Height h ₁	mm	290	440	420	370
The Dimension Of Table Size (L*B)	mm	850x500x50	1010x520x50	1000x510x55	910x500x53
Caster Wheel d	mm	φ 125x40	φ 150x48	φ 147x50	φ 125x40
Overall Length L ₁	mm	1145	1305	1345	1210
Height Of Handle From The Ground h ₂	mm	920	970	935	920
Lifting speed with load/without load	mm/s	65/94	65/94	70/80	90/110
Lowering speed with load/without load	mm/s	98/74	98/74	50/35	100/90
Lifting Cycle (fully charged)		120	100	100	100
Battery		2x12/15	2x12/24	2x12/15	2x12/15
Vertical Travel h ₃	mm	590	585	550	930
Lifting Motor (DC24V KW)		0.8	0.8	0.8	0.8
Charger (built-in)24V3A		8.5Hr	8.5Hr	8.5Hr	8.5Hr
Approx Lifting Speed		10	10	12	10
Net Weight	Kg	115	157	160	142



350kg capacity
1.3m Height
Table:910x500mm
Double scissor lift

Ideally suited for use as a feeding table on an assembly line.

Excellent hydraulic unit for raising table top to desired height.

Electrically operated table descent control.

Industrial Equipment